952

0 0				
Source ID	DBS	FN	QPC	S E r
				P N s
				H C v
				DBC

910

1 0		
FMT	FDF	SYT/FDF

906

954

908

909

Actual data

905

FIG. 1

FIG. 2

FIG. 3A

208 operation code

	msb		lsb
opcode	Authentication and Key exchange		
operand[0]	F_{15}	algorithm ID	200
operand[1]	FF_{16}		
operand[2]	FF_{16}		
operand[3]	FF_{16}		
operand[4]	FF_{16}		
operand[5]	FF_{16}		
operand[6]	FF_{16}		
operand[7]	FF_{16}		
operand[8]	FF_{16}		

FIG. 3B

208 operation code

	msb		lsb
opcode	Authentication and Key exchange		
operand[0]	0	algorithm ID	200
operand[1]	(msb)	algorithm field	201
operand[2]			(lsb)
operand[3]	FF_{16}		
operand[4]	FF_{16}		
operand[5]	FF_{16}		
operand[6]	FF_{16}		
operand[7]	(msb)	maximum data length	212
operand[8]			(lsb)

FIG. 3C

208 Operation code

	msb		lsb
opcode	Authentication and Key exchange		
operand[0]	reserved	algorithm ID	200
operand[1]	(msb)	algorithm field	201
operand[2]			(lsb)
operand[3]	label 202	step No.	203 / 299
operand[4]	subfunction		204
operand[5]	channel No.		206
operand[6]	block No. 205	total block No.	209
operand[7]	(msb)	data_length	
operand[8]			(lsb)
operand[9]			207
operand[8+ data_length]	data		

Receiving device   Sending device   Time

AKE status command 300

AKE response 301

Make-response command 302

Response 303

Verify-me command 304

Response 305

Make-response command 306

Response 307

Verify-me command 308

Response 309

Create-key-information command 310

Response 311

Reconstruct-key command 312

Response 313

FIG. 4

907

| Data length | Tag | Channel | Tcode | Sy |

900

Header CRC — 901

906

904 {

| 0 | 0 | Source ID | DBS | FN | QPC | SPH | rsv | DBC |
| 1 | 0 | FMT | FDF | FDF/SYT | | | | |

908   909

902

Actual data

905

Data CRC — 903

← 4 Bytes →

FIG. 5   PRIOR ART

16229J1PCTE1A.doc 1999/9/26   31

Reference numerals

|		
	100	signal source
	101	encrypter
	102	source packet generator
5	103	CIP block generator
	107	isochronous packet generator
	108, 127	1394 packet I/O means
	105	output command
	109, 126	encryption key
10	110	sending device
	128	receiving device
	111	IEEE 1394 bus
	106, 125	key generator
	120	AV generator
15	121	decrypter
	122	actual data extractor
	123	payload extractor
	200	algorithm ID
	201	algorithm field
20	202	label
	203	step No.
	204	channel No.
	205	block No.
	206	total block No.
25	207	data
	208	operation code

209	data length
212	maximum data length
299	subfunction
300	AKE status command
301	AKE response
302, 306	make-response command
303, 305, 307, 309, 311, 313	response
304, 308	verify-me command
310	create-key-information command
312	reconstruct-key command
900	isochronous packet header
901	header CRC
902, 952	isochronous payload
903	data CRC
904, 954	CIP header
905	actual data
906	source ID
907	tag
908	FMT
909	FDF
910	encrypting information (ENC)
952	isochronous payload